

MULTIMINILED 12V / 24V DIM/NO DIM



PTDC/80/B
PTDCD/80



Strip LED




Codice Code	LPH ↓↑mm	Vdc IN	DIM	Vac IN	DIM	Hz	REGA?	IC	ta °C	tc °C	PFC	Euro Cad.
PTDC/80/B	230x51x40	176-264	NO	220-240	NO	50/60	15	25A 200µS	-20..40	75	OK	66,00
PTDCD/80	230x51x40	176-264	S10 - R P	220-240	S10 - R P	50/60	15	25A 200µS	-20..40	75	OK	68,00

PTDC/80/B - PTDCD/80



Vout	Vdc	12	24
Power	W	50	80

Dimensioni (mm) - Dimensions (mm)



PTDC/100/B
PTDCD/100



Strip LED




Codice Code	LPH ↓↑mm	Vdc IN	DIM	Vac IN	DIM	Hz	REGA?	IC	ta °C	tc °C	PFC	Euro Cad.
PTDC/100/B	230x51x40	176-264	NO	220-240	NO	50/60	15	25A 200µS	-20..40	75	OK	68,00
PTDCD/100	230x51x40	176-264	S10 - R P	220-240	S10 - R P	50/60	15	25A 200µS	-20..40	75	OK	70,00

PTDC/100/B - PTDCD/100



Vout	Vdc	12	24
Power	W	60	100

Dimensioni (mm) - Dimensions (mm)



TRAF0 LED TBT 12V


Trasformatore elettronico dimmerabile per lampade LED e alogene 12Vac
Dimmable electronic transformer for LED and HALO 12Vac lamps



MICRO LED TRAF0 105 PFS



Dimensioni (mm) - Dimensions (mm)



Codice Code	LPH ↓↑mm	Vac IN	DIM	Carico Load	W	Hz	ta °C	tc °C	Vout Vac	Euro Cad.
RN9140	120x39x28	220-240	C	HALO	20±105	50/60	-15...50	80	12	16,50
				LED *	3÷55					



Lampada alogena tradizionale
Traditional halogen lamp
12Vac - 20±105W



Lampada LED - LED lamp
12Vac - 3÷55W
* Max 3 Lamps



Alimentatori LED - Strisce LED - LED Driver - Strip LED

Components

